



## ASR-010D (1D Barcode Scanner)



Model Name		ASR-010D
Barcode	Reading method	CCD linear image sensor - 1,500 pixels
	Minimum resolution	0.127 mm (0.005 inch)
	Reading distance	70~210 mm (2.76~8.27 inch) (*1)
	Reading angle	Pitch: $\pm 65^\circ$ Roll: $\pm 25^\circ$ Skew: $\pm 50^\circ$
	Readable barcodes	JAN, UPC/EAN, CODE11, CODE39, CODE93, CODE128, I TF (INTERLEAVED 2of5), D ISCRETE 2of5, CHINESE 2of5, M ATRIX 2of5, CODEBAR (NW-7), MSI, GS1 DATABAR OMNIDIRECTIONAL, GS1 DATABAR LIMITED, GS1 DATABAR EXPENDED
	Light source	Red LED
Power source	Battery capacity	Built-in rechargeable lithium-ion battery (700mAh)
	Number of scans	About 40,000 (*2)
	Charging method	Magconn™ cable (*3)
	Charging time	About 2 hours (built-in battery) (*4)
Key input		2 trigger key
Communication	Interface	MFi on Lightning (*5)
Appearance	Dimensions (W)x(D)x(H)	63.7 * 9.7 * 117.2 mm (2.51 * 0.38 * 4.61 inch) (*6)
	Weight (with battery)	About 65g
	Material	PC
	Casing color	White
	LED display	Blue LED: Connected with device /Blinking Blue LED: Reading/Red LED: Battery is charging/Faint Red LED: Battery is fully charged
Environment	Operating temperature	-10~45 C, 20~85 % RH (Charge at 0 C or more, however)
	Storage temperature	-20~60 C, 10~95 % RH
	IP Rating	IP54 compliant
	Anti-drop	(Six-sided * 4 edge, once each) 1.5 m (59.06 inch) (*7)
Certificate		Apple MFi / FCC / CE / RoHS
Bundled items		Magconn™ cable / Earphone extension cable / User manual

\*1 Differs per barcode type.

\*2 Number of times when the BEEP sound, vibration and illumination are all set to ON. 4.5h continuous reading on iPhone®'s default brightness setting.

\*3 Standard iPhone® 2A charger is strongly recommended to be used when using Magconn™ cable.

\*4 iPhone® and AsReader battery will be recharged simultaneously. iPhone® and AsReader battery will be recharged in 3.5h and 2h respectively in simultaneous recharging mode.

\*5 A specialised SDK for communication via Lightning is available for download.

\*6 Excluding protrusions \*7 Depending on the drop angle, the iPhone® screen may break.

• For the latest information, please visit our website. • iPhone®, iPad® and iPod touch® are registered trademarks of Apple® Inc. • AsReader® is a registered trademark of Asterisk Inc.

<https://AsReader.com>

AsReader, Inc. U.S. Head Sales Office 920 SW 6th Ave., Ste 1200, Portland, OR 97204-1212 USA Tel: +1 (503) 770 2777  
 AsReader Europa B.V. Stationsplein 45, A4.004, 3013 AK Rotterdam, The Netherlands Tel: +31 (0) 10 808 0488  
 Dalian Mingrix Technology Co., Ltd. R901, Heyi Building, No.6, Aixian Street, Dalian High-tech Industrial Zone, 116023, P.R. China Tel: +86 (0) 411 8445 8656  
 Asterisk Inc. Shin-Osaka Dainichi Bldg. 201, 5-6-16 Nishinakajima, Yodogawa-ku, Osaka-city, 532-0011, Japan Tel: +81 (0) 50 5536 1185



## ASR-010D (1D Barcode Scanner)



Model Name		ASR-010D
Barcode	Reading method	CCD linear image sensor - 1,500 pixels
	Minimum resolution	0.127 mm (0.005 inch)
	Reading distance	70~210 mm (2.76~8.27 inch) (*1)
	Reading angle	Pitch: $\pm 65^{\circ}$ Roll: $\pm 25^{\circ}$ Skew: $\pm 50^{\circ}$
	Readable barcodes	JAN, UPC/EAN, CODE11, CODE39, CODE93, CODE128, I TF(INTERLEAVED 2of5), D ISCRETE 2of5, CHINESE 2of5, M ATRIX 2of5, CODEBAR(NW-7), MSI, GS1 DATABAR OMNIDIRECTIONAL, GS1DATABAR LIMITED, GS1DATABAR EXPENDED
	Light source	Red LED
Power source	Battery capacity	Built-in rechargeable lithium-ion battery (700mAh)
	Number of scans	About 40,000 (*2)
	Charging method	Magconn™ cable (*3)
	Charging time	About 2 hours (built-in battery) (*4)
Key input		2 trigger key
Communication	Interface	MFi on Lightning (*5)
Appearance	Dimensions (W)x(D)x(H)	63.7 * 9.7 * 117.2 mm (2.51 * 0.38 * 4.61 inch) (*6)
	Weight (with battery)	About 65g
	Material	PC
	Casing color	White
	LED display	Blue LED: Connected with device /Blinking Blue LED: Reading/Red LED: Battery is charging/Faint Red LED: Battery is fully charged
Environment	Operating temperature	-10~45 C, 20~85 % RH (Charge at 0 C or more, however)
	Storage temperature	-20~60 C, 10~95 % RH
	IP Rating	IP54 compliant
	Anti-drop	(Six-sided * 4 edge, once each) 1.5 m (59.06 inch) (*7)
Certificate		Apple MFi / FCC / CE / RoHS
Bundled items		Magconn™ cable / Earphone extension cable / User manual

\*1 Differs per barcode type.

\*2 Number of times when the BEEP sound, vibration and illumination are all set to ON. 4.5h continuous reading on iPhone®'s default brightness setting.

\*3 Standard iPhone® 2A charger is strongly recommendd to be used when using Magconn™ cable.

\*4 iPhone® and AsReader battery will be recharged simultaneously. iPhone® and AsReader battery will be recharged in 3.5h and 2h respectively in simultaneous recharging mode.

\*5 A specialised SDK for communication via Lightning is available for download.

\*6 Excluding protrusions \*7 Depending on the drop angle, the iPhone® screen may break.

· For the latest information, please visit our website. · iPhone®, iPad® and iPod touch® are registered trademarks of Apple® Inc. · AsReader® is a registered trademark of Asterisk Inc.

<https://AsReader.com>